



Oil Pattern Distance	46	Reverse Brush Drop	38	Oil Per Board	Multi ul
Forward Oil Total	17.795 mL	Reverse Oil Total	10.34 mL	Volume Oil Total	28.135 mL
Tank Configuration	Multi Tank	Tank A Conditioner	Fire	Tank B Conditioner	Ice

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	12L	12R	3	60	18	4	A	51	0.0	5.1	5.1	3060
2	2L	2R	3	55	18	4	A	111	5.1	12.7	7.6	6105
3	8L	8R	2	55	18	4	A	50	12.7	17.8	5.1	2750
4	10L	10R	3	50	22	3	A	63	17.8	27.1	9.3	3150
5	12L	12R	2	45	22	3	A	34	27.1	33.3	6.2	1530
6	13L	13R	2	40	22	3	A	30	33.3	39.5	6.2	1200
7	2L	2R	0	40	26	2	A	0	39.5	46.0	6.5	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	55	22	3	B	0	46.0	28.0	-18.0	0
2	14L	14R	2	55	22	3	B	26	28.0	21.8	-6.2	1430
3	13L	13R	2	55	18	3	B	30	21.8	16.7	-5.1	1650
4	12L	12R	2	60	18	3	B	34	16.7	11.6	-5.1	2040
5	6L	6R	3	60	14	3	B	87	11.6	5.7	-5.9	5220
6	2L	2R	0	60	14	4	B	0	5.7	0.0	-5.7	0



Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle:Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.46	2.08	1.02	1.02	2.08	5.46

