

Nutmeg NEBA (2020)



Oil Pattern Distance **Forward Oil Total Tank Configuration**

18.55 mL Only A

40

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

36 8.3 mL **Navigate** Oil Per Board **Volume Oil Total Tank B Conditioner**

50 ul 26.85 mL **Navigate**

	START	STOP	LOADS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	14	3	111	0.0	3.9	3.9	5550
2	7L	7R	2	14	3	54	3.9	7.8	3.9	2700
3	9L	9R	2	14	3	46	7.8	11.7	3.9	2300
4	11L	11R	4	14	3	76	11.7	19.6	7.9	3800
5	13L	13R	3	18	3	45	19.6	27.2	7.6	2250
6	14L	14R	3	18	3	39	27.2	34.8	7.6	1950
7	2L	2R	0	30	3	0	34.8	40.0	5.2	0

	START	STOP	LOADS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	0	40.0	30.0	-10.0	0
2	15L	15R	3	18	3	33	30.0	22.4	-7.6	1650
3	13L	13R	3	18	3	45	22.4	14.8	-7.6	2250
4	12L	12R	3	18	3	51	14.8	7.2	-7.6	2550
5	2L	2R	1	18	3	37	7.2	4.7	-2.5	1850
6	2L	2R	0	18	3	0	4.7	0.0	-4.7	0
6	2L	2R	0	18	3	0	4.7	0.0	-4.7	

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Description Outside:Middle		Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	6.14	2,76	1.07	1.07	2.76	6.14



