

NEBA Masters-Long



Oil Pattern Distance **Forward Oil Total Tank Configuration**

45 22.52 mL Only A

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

40 7.04 mL Oil Per Board **Volume Oil Total Tank B Conditioner**

40 ul 29.56 mL

1 2L 2R 8 10 3 296 0.0 9.9 9.9 11840 2 2L 2R 2 10 3 74 9.9 12.7 2.8 2960 3 5L 5R 2 10 3 62 12.7 15.5 2.8 2480 4 7L 7R 1 14 3 27 15.5 17.4 1.9 1080 5 10L 10R 2 14 3 42 17.4 21.3 3.9 1680 6 12L 12R 1 14 3 17 21.3 23.2 1.9 680 7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560 10 2L </th <th>2 2L 2R 2 10 3 74 9.9 12.7 2.8 296 3 5L 5R 2 10 3 62 12.7 15.5 2.8 248 4 7L 7R 1 14 3 27 15.5 17.4 1.9 108 5 10L 10R 2 14 3 42 17.4 21.3 3.9 168 6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36</th>	2 2L 2R 2 10 3 74 9.9 12.7 2.8 296 3 5L 5R 2 10 3 62 12.7 15.5 2.8 248 4 7L 7R 1 14 3 27 15.5 17.4 1.9 108 5 10L 10R 2 14 3 42 17.4 21.3 3.9 168 6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
3 5L 5R 2 10 3 62 12.7 15.5 2.8 2480 4 7L 7R 1 14 3 27 15.5 17.4 1.9 1080 5 10L 10R 2 14 3 42 17.4 21.3 3.9 1680 6 12L 12R 1 14 3 17 21.3 23.2 1.9 680 7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	3 5L 5R 2 10 3 62 12.7 15.5 2.8 248 4 7L 7R 1 14 3 27 15.5 17.4 1.9 108 5 10L 10R 2 14 3 42 17.4 21.3 3.9 168 6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 2 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
4 7L 7R 1 14 3 27 15.5 17.4 1.9 1080 5 10L 10R 2 14 3 42 17.4 21.3 3.9 1680 6 12L 12R 1 14 3 17 21.3 23.2 1.9 680 7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	4 7L 7R 1 14 3 27 15.5 17.4 1.9 108 5 10L 10R 2 14 3 42 17.4 21.3 3.9 168 6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
5 10L 10R 2 14 3 42 17.4 21.3 3.9 1680 6 12L 12R 1 14 3 17 21.3 23.2 1.9 680 7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	5 10L 10R 2 14 3 42 17.4 21.3 3.9 168 6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
6 12L 12R 1 14 3 17 21.3 23.2 1.9 680 7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	6 12L 12R 1 14 3 17 21.3 23.2 1.9 68 7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
7 15L 15R 2 14 3 22 23.2 27.1 3.9 880 8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	7 15L 15R 2 14 3 22 23.2 27.1 3.9 88 8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
8 16L 16R 1 14 3 9 27.1 29.0 1.9 360 9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	8 16L 16R 1 14 3 9 27.1 29.0 1.9 36
9 17L 17R 2 14 3 14 29.0 32.9 3.9 560	
10 2L 2R 0 22 3 0 32.9 45.0 12.1 0	9 17L 17R 2 14 3 14 29.0 32.9 3.9 56
	10 2L 2R 0 22 3 0 32.9 45.0 12.1

Г	START	STOP	LOADS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	3	0	45.0	20.0	-25.0	0
2	11L	11R	1	14	3	19	20.0	18.1	-1.9	760
3	9L	9R	1	14	3	23	18.1	16.2	-1.9	920
4	6L	6R	1	14	3	29	16.2	14.3	-1.9	1160
5	3L	3R	3	14	3	105	14.3	8.4	-5.9	4200
6	2L	2R	0	14	3	0	8.4	0.0	-8.4	0
ı										

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	1.82	1,38	1.13	1.13	1,38	1,82



